Technical data sheet

Falling vertical bend for PYROLINE® Con S BSKH09-K0521 fire protection duct

Item number: 7215664





Falling vertical bend for PYROLINE® Con S fire protection duct, type BSKH09-K0521, consisting of fibreglass lightweight concrete which is resistant to water and frost for the creation of vertical changes of direction (45°) of the duct. Mounted connectors ensure quick mounting in situ, whilst loosely placed covers ensure quick inspection and reassignment.

Including connection screws and sealing strips. Including connection screws and sealing strips.



Fibreglass lightweight concrete

| Master data | | | |
|-------------|---------------------|---------------------------------|--|
| | Item number | 7215664 | |
| | Туре | BSKH09-VF0521 | |
| | Description 1 | Vertical bend falling | |
| | Description 2 | for BSKH09-K0521 | |
| | Manufacturer | OBO | |
| | Dimension | 50x210 | |
| | Colour | Grey | |
| | Material | Fibreglass lightweight concrete | |
| | Smallest sales unit | 1 | |
| | Unit of quantity | Piece | |
| | Weight | 925 kg | |
| | Weight unit | kg/100 pc. | |

Technical data sheet

Falling vertical bend for PYROLINE® Con S BSKH09-K0521 fire protection duct Item number: 7215664



Dimensions 338 External dimensions 338 x 140 202 Internal dimensions 210 x 50 Width 338 mm Dimension B 338 mm Dimension b 210 mm Dimension h 50 mm Dimension H 140 mm 202 mm Dimension L

| Technical data | | |
|----------------|--|----------------------------------|
| | Number of flammable sides | 4 |
| | Cover fastening | Loose |
| | Fire resistance class E – function maintenance | 30 |
| | Fire resistance class I – installation duct | 90 |
| | With perforation | no |
| | Partitions possible | yes |
| | Jacketing | Without |
| | Material of the insulation | Glass-fibre lightweight concrete |
| | Angle of the bend | 45 ° |