Technical data sheet

Rising vertical bend for PYROLINE® Con S BSKH09-K0521 fire protection duct

Item number: 7215654





Rising vertical bend for PYROLINE® Con S fire protection duct, type BSKH09-K0521, consisting of fibreglass lightweight concrete which is resistant to water and frost for the creation of vertical changes of direction (45°) of the duct. Mounted connectors ensure quick mounting in situ, whilst loosely placed covers ensure quick inspection and reassignment.

Including connection screws and sealing strips. Including connection screws and sealing strips.



Fibreglass lightweight concrete

Master data		
	Item number	7215654
	Туре	BSKH09-VS0521
	Description 1	Vertical bend rising
	Description 2	for BSKH09-K0521
	Manufacturer	OBO
	Dimension	50x210
	Colour	Grey
	Material	Fibreglass lightweight concrete
	Smallest sales unit	1
	Unit of quantity	Piece
	Weight	905 kg
	Weight unit	kg/100 pc.

Technical data sheet

Rising vertical bend for PYROLINE® Con S BSKH09-K0521 fire protection duct Item number: 7215654



Dimensions External dimensions 338 x 140 Internal dimensions 210 x 50 Width 338 mm Dimension B 338 mm Dimension b 210 mm 210 338 204 Dimension h 50 mm Dimension H 140 mm 204 mm Dimension L

Technical data		
	Number of flammable sides	4
	Cover fastening	Loose
	Fire resistance class E – function maintenance	30
	Fire resistance class I – installation duct	90
	With perforation	no
	Partitions possible	yes
	Jacketing	Without
	Material of the insulation	Glass-fibre lightweight concrete
	Angle of the bend	45 °