

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 58 mm

Item number: 7400293



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking lid. With separating retainer in the trunking base. Only compatible with the UZD250-4/350-4.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St Steel

FS Strip galvanized

Master data

Item number	7400293
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x350x58
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	422.969 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	350 mm
Height	58 mm
Dimension a	120 mm
Dimension b	110 mm
Dimension h	58 mm

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height
58 mm

Item number: 7400293



Technical data

Number of fixed partitions	2
Number of compartments	3 St.
Mounting system fastening type	Floor
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	350 mm
Duct height, min.	58 mm
Usable cross-section	18794 mm ²
Removable cover	yes
Cross-section, draw a	6341 mm ²
Cross-section, draw b	6112 mm ²